

SR- ROOF PANEL CLIP W/
 () ¼ - 14 x 2" TEK 3 W/O WASHER
 PER CLIP, PER PANEL AT EACH LAP
 SECONDARY SUPPORT

¼ - 14 x 7/8" STITCH
 TEKS 2 ½" O/C AT LAP

NOTE: BUTYL SEALANT
 AND BUTYL TAPE TO RUN
 ACROSS FULL WIDTH OF
 PANELS; NOT SHOWN AT
 HIGH RIBS FOR CLARITY.

1" x 3/32" BUTYL TAPE SEALANT

SUPPORT ANGLE AND
 FASTENERS BY OTHERS
 (NOT BY IMP SUPPLIER)

SECONDARY FRAMING
 (NOT BY IMP SUPPLIER)

CONTINUOUS ½" Ø BEAD OF
 GUN-GRADE NON-SKINNING BUTYL
 SEALANT AT PANEL END-LAP

FIELD-APPLIED ¼" BEAD
 OF NON-SKINNING BUTYL
 SEALANT AT SR OVERLAP

NOTE: REFER TO
 SECTION 13.6 ON
 SHEET 8 OF 10 ON
 SR2 & SR3 INSULATED
 ROOF PANELS
 GENERAL
 INSTALLATION GUIDE
 FOR ADDITIONAL
 INFORMATION.

FIELD-APPLIED ⅛" BEAD
 OF BUTYL SEALANT ON
 UNDERSIDE OF SR CLIP

FACTORY-APPLIED FOAM GASKET
 AT UNDERSIDE OF SR ROOF CLIP

NOTE: DO NOT OVER-DRIVE FASTENERS. IF
 THE METAL AT THE EDGE OF THE PANEL IS
 DEFORMED OUT OF PLANE, THE ADJACENT
 PANEL WILL BE DIFFICULT TO ENGAGE AND
 WILL NOT SEAM. AFTER SR CLIP HAS BEEN
 INSTALLED OVER MALE LEG OF STANDING
 SEAM PANEL, PRE-CRIMP, USING ½" HAND
 CRIMPING TOOL.

SR ROOF PANEL END-LAP

(SECTION VIEW)

DETAIL:	SR ROOF PANEL END-LAP
APPLICATION:	COMMERCIAL & INDUSTRIAL - SR ROOF
DATE:	05/19/17
JOB NO.:	N/A
DRAWN:	MMF
SHEET:	1 OF 1

US: (888) 970-2947
 CA: (800) 265-6583 (English)
 CA: (800) 567-2582 (French)
 WWW.AWIPANELS.COM

ALL WEATHER
 INSULATED PANELS

