

RD1-Hidden Allowable Load Table (PSF) for Three or More Spans

Panel Strength and Deflection Limit Criteria

Panel Thickness	Panel Span (ft)										
	3'-0"	3'-6"	4'-0"	4'-6"	5'-0"	5'-5"	6'-0"	6'-6"	7'-0"	7'-6"	8'-0"
2"	72	61	52	46	40	36	32	29	26	23	21
2.5"	90	76	65	58	51	45	41	37	33	30	28
3"	106	90	77	68	61	55	50	45	41	37	34
4"	136	115	100	88	78	70	64	59	54	50	47
5"	162	138	119	105	94	84	77	70	65	60	56
6"	185	157	136	120	107	96	88	80	74	69	64
8"	218	185	161	142	127	114	104	95	88	81	76

Connection Strength Criteria - Fasteners with WC-01 Clips at Side Joint

Fastening Pattern	Support Thickness	Panel Span (ft)										
		3'-0"	3'-6"	4'-0"	4'-6"	5'-0"	5'-5"	6'-0"	6'-6"	7'-0"	7'-6"	8'-0"
(2) Fasteners per clip	16 gauge	50	42	37	32	29	26	24	22	20	19	18
	14 gauge	66	56	49	43	38	35	32	29	27	25	23
	12 gauge or 3/16"	70	60	52	46	41	37	34	31	29	27	25
(3) fasteners per clip	16 gauge	70	60	52	46	41	37	34	31	29	27	25
	14 gauge	70	60	52	46	41	37	34	31	29	27	25

Notes:

1. Load span table is based on Allowable Stress Design (ASD).
2. Table is based on values derived from transverse load testing per ASTM E72, ASTM E1592 and strength of fasteners.
3. Panel Properties are based on **26 gauge exterior** and **26 gauge interior** facings. Inquire about other gauges.
4. The lowest load between Panel Strength, Deflection Limit and Connection Strength shall be used to determine spans.
5. The deflection limit criteria is $L/240$.
6. Connection based on $\frac{1}{4}$ -14 or $\frac{1}{4}$ -20 DP3 or DP5 self-drilling fasteners with WC-01 clip installed into min. 16 gauge or 12 gauge steel.
7. Safety Factor = 2.5 for buckling, 3.0 for core shear, 2.0 for wall clip, 3.0 for fastening pullover/pullout.
8. White single-ply roofing membrane or single skin roof panels must be installed over the IMP for weatherproofing. See the OneDek Design Guide for membrane allowable loads.
9. Panel weights can be found on a separate Panel Weights Table.
10. Structural design of roof supports has not been considered and must be designed the support professional.
11. Thermal effects from controlled environment and cold storage applications have not been considered.
12. Load tables do not account for sliding snow/drag loads.
13. Load table for pressure assumes a minimum purlin bearing width of 2.5". For 6" thick panels, maximum loads can be increased for larger purlin widths. Consult your AWIP representative for more information.
14. In Canada, to use load table for pressure, calculate total factored load as per NBCC load combinations, divide by 1.5, and compare to values in the table.
Example: $(1.25 \times \text{panel wt.} + 1.5 \times \text{snow load/LL} + 0.4 \times \text{downward wind})/1.5$.
15. In Canada, for wind uplift use specified wind loads calculated as per NBCC and compare to load table values.
16. Consult your AWIP representative for project specific calculations.
17. Consult your AWIP representative for design per FM Global Loss Prevention Data Sheet 1-28 and FM 4881 requirements.
18. Load tables are subject to change without notice – visit www.awipanel.com for the latest information.



All Weather
Insulated Panels



Scan for the most current
product information

1 (888) 970-AWIP (2947)
awipanel.com
sales@awipanel.com



In accordance with ongoing efforts to improve our products and their performance, All Weather Insulated Panels reserves the right to change without notice the specifications contained herein. The contents herein are for general information and illustrative purposes only and are not intended to serve as any type of advice. Every effort is made to ensure the accuracy of the information included in this brochure and it is believed that the information contained herein is accurate and reliable as of the date of this publication. All Weather Insulated Panels does not warrant or represent the accuracy or reliability of any information included in this collateral. Any reliance of any information without consultation with All Weather Insulated Panels or a duly authorized representative shall be at the user's own risk. Copyright 2025 All Weather Insulated Panels—All rights reserved.