

NOTE: REFER TO JOINERY STITCH FASTENING DETAIL ON SHEET \_\_.

BUTYL SEALANT AT VERTICAL JOINT

"BT-03" BASE TRIM W/  
POP RIVETS 12" O/C  
(SET TRIM IN BUTYL SEALANT)

1/4"

( ) 1/4 - 14 x \_ TEK 3 FASTENER  
W/ 1 1/8" BONDED WASHER  
PER PANEL, AT EACH  
SECONDARY SUPPORT (SEE  
WALL FASTENING LAYOUT)

"BA-01" BASE ANGLE

"BF-01" ZEE FLASHING  
(FIELD-SLOPE TO DRAIN)

CONCRETE ANCHORS  
(NOT BY IMP SUPPLIER)

SET ZEE FLASHING IN  
BUTYL SEALANT

CONTINUOUS BUTYL SEALANT  
(MARRY TO VERTICAL SEALANT)

# # BASE CONDITION - FLUSH

(SECTION VIEW)

DETAIL:

## BASE CONDITION - FLUSH

APPLICATION:  
VERTICAL FIRE WALL, COMMERCIAL & INDUSTRIAL  
AWIP DETAIL NUMBER:  
MWW-ACH-BC-001

929 ALDRIDGE ROAD  
VACAVILLE, CA 95688  
TEL: (707) 359-2280  
FAX: (707) 359-2286  
WWW.AWIPANELS.COM



DATE:  
04/02/19

SHEET:

DRAWN BY:  
MMF

1 OF 1