

**NOTE: REFER TO JOINERY
STITCH FASTENING DETAIL
ON SHEET __.**

**RUN "JT-" JAMB TRIM UP
PAST PANEL EDGE HEIGHT
SO "BT-" UNIVERSAL L
LAPS OVER AT TRANSITION**

"BT-" UNIVERSAL L

EDGE OF PANEL LINE

(TRANSITION DETAIL)

BUTYL SEALANT AT
VERTICAL JOINT

() 1/4 - 14 x _ TEK 3
POLARFAST FASTENER PER
PANEL (SEE WALL
FASTENING LAYOUT)

"BT-02" UNIVERSAL L W/
POP RIVETS 12" O/C
(SET TRIM IN BUTYL
SEALANT)

1/4"

CONTINUOUS BUTYL SEALANT
(NOT BY IMP SUPPLIER)

FRAMED OPENING
(NOT BY IMP SUPPLIER)

"DF-02" DRIP FLASHING

CONTINUOUS BUTYL SEALANT
(MARRY TO VERTICAL SEALANT)

DOOR / WINDOW FRAME
& EXPOSED SEALANTS
(NOT BY IMP SUPPLIER)

FRAMED OPENING ONE PIECE HEADER

(SECTION VIEW)

DETAIL:

FRAMED OPENING - HEADER

APPLICATION:
VERTICAL FIRE WALL, COMMERCIAL & INDUSTRIAL
AWIP DETAIL NUMBER:
MWW-ACH-FO-001

DATE:
04/02/19
DRAWN BY:
MMF

SHEET:
1
OF
1

929 ALDRIDGE ROAD
VACAVILLE, CA 95688
TEL: (707) 359-2280
FAX: (707) 359-2286
WWW.AWIPANELS.COM

