

NOTE: FIELD REMOVE FOAM AND LINER AT CUTBACK.

FIELD-FILL W/ COMPRESSIBLE INSULATION
(NOT BY IMP SUPPLIER)

SR_ INSIDE CLOSURE STRIP
W/ $\frac{3}{4}$ " x $\frac{3}{32}$ " BUTYL TAPE
SEALANT AT TOP & BOTTOM

$\frac{1}{4}$ -14 x 0.88" HWH DP1 6" O/C

"LE_ S" LOW EAVE TRIM

POP RIVET 12" O/C

"WC-01" PANEL CLIP W/
(_) $\frac{1}{4}$ - 14 x _ HWH DP3 W/O
WASHER AT PANEL JOINT

BUTYL SEALANT AT
VERTICAL JOINT

3"

SR_ ROOF PANEL CLIP W/
(_) $\frac{1}{4}$ - 14 x 2" HWH DP3 W/O WASHER,
PER CLIP, PER PANEL AT EAVE STRUT

BUTYL TAPE SEALANT

BUTYL TAPE SEALANT (MARRY
TO VERTICAL SEALANT)


EAVE STRUT
(NOT BY IMP SUPPLIER)

NOTE: DO NOT OVER-DRIVE FASTENERS. IF THE METAL AT THE EDGE OF THE PANEL IS DEFORMED OUT OF PLANE, THE ADJACENT PANEL WILL BE DIFFICULT TO ENGAGE AND WILL NOT SEAM. AFTER SR CLIP HAS BEEN INSTALLED OVER MALE LEG OF STANDING SEAM PANEL, PRE-CRIMP, USING $\frac{1}{2}$ " HAND CRIMPING TOOL.

#

GUTTERLESS EAVE

(SECTION VIEW)



DETAIL: GUTTERLESS EAVE

APPLICATION:
SR ROOF, COMMERCIAL & INDUSTRIAL
AWIP DETAIL NUMBER:
SRR-ACI-GE-001

929 ALDRIDGE ROAD
VACAVILLE, CA 95688
TEL: (707) 359-2280
FAX: (707) 359-2286
WWW.AWIPANELS.COM



SHEET:
DATE:
DRAWN BY:

1 OF 1
MMF