

APPLY CONTINUOUS BEAD OF NON-SKINNING BUTYL SEALANT AND MARRY VERTICAL JOINT TO OTHER SEALED CONNECTIONS (I.E. WINDOWS & DOORS) AS NECESSARY TO EFFECT A COMPLETE WEATHER BARRIER.

"WC-01" PANEL CLIP W/ $\frac{1}{4}$ " Ø HWH DP W/O WASHER (SEE PANEL JOINT AND INTERMEDIATE SUPPORT DETAILS FOR FASTENING REQUIREMENTS)

NOTE: REFER TO CONNECTION DETAILS FOR SPECIFIC LOCATION(S) OF MARRIAGE BEAD(S).

CONTINUOUS SEALANT / TAPE ALONG PERIMETER FRAMING (NOT REQUIRED AT ALL FRAMING MEMBERS, REFER TO CONNECTION DETAILS FOR SPECIFIC LOCATION(S))

INTERIOR

SECONDARY FRAMING MEMBER

FIELD APPLIED NON-SKINNING BUTYL SEALANT AT VERTICAL JOINT

EXTERIOR

MARRIAGE BEAD DETAIL

(ISOMETRIC VIEW)

DETAIL:

MARRIAGE BEAD

APPLICATION:
VERTICAL WALL, COMMERCIAL & INDUSTRIAL

AWIP DETAIL NUMBER:

AVW-ACI-MB-001

929 ALDRIDGE ROAD
VACAVILLE, CA 95688
TEL: (707) 359-2280
FAX: (707) 359-2286
WWW.AWIPANELS.COM

All Weather
Insulated Panels



SHEET:

DATE:
10/31/23

DRAWN BY:
MMF

1

OF
1