

HR_ INSIDE CLOSURE STRIP
W/ 3/4" x 3/32" BUTYL TAPE
SEALANT AT TOP & BOTTOM

"GH-01" GUTTER HANGER AT
INTERIOR HI-RIBS 40" O/C
ATTACH W/ (4) 1/4 -14 x 0.88"
HWH DP1

1/4 -14 x 0.88" HWH
DP1 6" O/C

"GT_ H" GUTTER TRIM

"BB-01" BIRD BLOCK W/
1/4 -14 x 0.88" HWH DP1 12" O/C

"WC-01" PANEL CLIP W/
() 1/4 - 14 x _ HWH DP3 W/O
WASHER AT PANEL JOINT

BUTYL SEALANT AT
VERTICAL JOINT

3"

1"

FIELD-FILL W/ COMPRESSIBLE
INSULATION
(NOT BY IMP SUPPLIER)

(3) 1/4 - 14 x _ HWH DP3 W/
WASHER, PER PANEL (SPACED
EVENLY)

BUTYL TAPE SEALANT


BUTYL TAPE SEALANT (MARRY
TO VERTICAL SEALANT)

EAVE STRUT
(NOT BY IMP SUPPLIER)

NOTE: FIELD-REMOVE FOAM
& LINER AT CUTBACK.

EAVE W/ GUTTER

(SECTION VIEW)



DETAIL:

EAVE WITH GUTTER

APPLICATION:

HR ROOF, COMMERCIAL & INDUSTRIAL

AWIP DETAIL NUMBER:

HRR-ACHLEG-001

929 ALDRIDGE ROAD
VACAVILLE, CA 95688
TEL: (707) 359-2280
FAX: (707) 359-2286
WWW.AWIPANELS.COM

All Weather
Insulated Panels



SHEET:

DATE:

10/23/23

DRAWN BY:

MMF

1 OF 1