

HR_ INSIDE CLOSURE STRIP
W/ 1" x 3/16" BUTYL TAPE
SEALANT AT TOP & BOTTOM

3"

FIELD-FILL W/ COMPRESSIBLE
INSULATION (NOT BY IMP SUPPLIER)

NOTE: FIELD-REMOVE FOAM
& LINER AT CUTBACK.

1/4 - 14 x 7/8" STITCH
TEKS 6" O/C

"LE-_" LOW EAVE TRIM

POP RIVETS 12" O/C

"WC-01" PANEL CLIP W/
(_) 1/4 - 14 x _ TEK 3 FASTENERS
W/O WASHER AT PANEL JOINT

"SW-01" SADDLE WASHER W/
1/4 - 14 x _ TEK 3 W/ WASHER
SPACED _ O/C (PILOT HOLE
RECOMMENDED)

BUTYL TAPE SEALANT

BUTYL TAPE SEALANT (MARRY
TO VERTICAL SEALANT)

EAVE STRUT
(NOT BY IMP SUPPLIER)

BUTYL SEALANT AT
VERTICAL JOINT

GUTTERLESS EAVE

(SECTION VIEW)

DETAIL:

GUTTERLESS EAVE

APPLICATION:
HR ROOF, COMMERCIAL & INDUSTRIAL
AWIP DETAIL NUMBER:
HRR-ACL-GE-001

929 ALDRIDGE ROAD
VACAVILLE, CA 95688
TEL: (707) 359-2280
FAX: (707) 359-2286
WWW.AWIPANELS.COM

ALL WEATHER
INSULATED PANELS



SHEET:
DATE: 01/13/20
DRAWN BY: MMF

1 OF 1