All Weather Insulated Panels

Pre-engineered edge metal solutions for OneDek®



Your vision. Our purpose.







Metal-Era products in a range of great-looking styles and colors for your building

With installation that's a snap compared to other roof edge designs, Metal-Era fascia products save you lots of time. Just as important, these prefabricated components come in a range of great-looking styles for your building. They're tested to the strictest building codes and are backed by some of the strongest warranties in the industry.

Product Specifications

Product Line	Anchor-Tite Standard Fascia	Anchor-Tite Drip Edge	Perma-Tite Gold Coping**	Seal-Tite WR Gutter	Seal-Tite Industrial Downspout	Seal-Tite LT Downspout
Versions	• Single-Ply	• Standard	• Tapered	• Chamfer	Closed Open Face	Corrugated
Standard Sizes	5.5", 7"	4.5", 6", 7.5"	Exterior 6" Interior 4"	7 3/4"	Min. 3" Max. 5.5"	Corrugated: 4"x5"
Wind Warranty	Lifetime, 215 MPH	Lifetime, 215 MPH	Lifetime, 215 MPH	30 Year, 160 MPH	5 Year Workmanship	5 Year Workmanship
Cover Materials	24 ga., 22 ga. .040"	24 ga., 22 ga. .040"	24 ga., 22 ga. .040", .050", .063"	24 ga., 22 ga., .040", .050", .063"	24 ga., .040"	24 ga., 22 ga., .032", .040"
Design Elements	Extruded Aluminum Anchor Bar Snap-on Cover 12 ft. Lengths	Extruded Aluminum Anchor Bar Snap-on Cover 12 ft. Lengths	16 ga. Anchor Clip Flush Face Profile Snap-on Cover	Extruded Aluminum Bracket 2-Piece Adjustable Bracket	Provided with Downspout Straps/ Hangers	Provided with Downspout Straps/ Hangers
ANSI/SPRI/FM 4435/ES-1 or ANSI/SPRI GT-1 Tested	X	X	X	X	NA	NA
FM Approved	X	X	X	X	NA	NA
Miami-Dade County Approved	×	X	X	X	NA	NA

^{**}Note: Tested Max Wall Width: 24" (.40"/24ga.) 32" (.050"/.063"/22ga.)



Anchor-Tite Advantages

- Lifetime, 215 MPH wind warranty
- Simple, snap-on design cover with need to strip-in or heat weld
- Prefabricated miters and accessories ensure proper fit and eliminate field fabrication
- Manufactured in 12' lengths with pre-punched holes to reduce installation time



Perma-Tite Gold Coping Advantages

- Lifetime, 215 MPH wind warranty
- Reduces labor time and costs with simple, snap-on installation
- Prefabricated miters, fasteners and accessories ensure proper fit and eliminate field fabrication
- Facilitates correct placement and proper thermal movement with slotted fastening holes



Seal-Tite WR Gutter Advantages

- Includes manufacturer's 30 Year, 160 MPH wind warranty
- ANSI/SPRI/GT-1 tested to comply with International Building Code
- Slotted fastening holes to ensure correct fastener placement and spacing
- Prefabricated miters, fasteners and accessories ensure proper fit and eliminate field fabrication

Express Colors*





Premium Colors



★ = Also in Mill Finish, **■** = Post-Painted, **△** = Must Specify Supplier, **★** = Available in 3 Other Stone Colors

Our colors are deep, rich and true. Made of Sherwin-Williams' Fluropon* High Performance Hylar 5000*/Kynar 500* finish, they offer the ultimate in resistance against fading and weathering. Custom colors are also available.





Scan for the most current product information



1 (888) 970-AWIP (2947) awipanels.com sales@awipanels.com









In accordance with ongoing efforts to improve our products and their performance, All Weather Insulated Panels reserve the right to change without notice the specifications contained herein. The contents herein are for general information and illustrate purposes only and are not intended to serve as any type of advice. Every effort is made to ensure the accuracy of the information included in this brochure and it is believed that the information contained herein is accurate and reliable as of the date of this publication. All Weather Insulated Panels does not warrant or represent the accuracy or reliability of any information included in this collateral. Any reliance of any information without consultation with All Weather Insulated Panels or a duly authorized representative shall be at the user's own risk. Copyright 2022 All Weather Insulated Panels — All rights reserved.