

FIELD-CUT  
THERMAL BREAK

SECONDARY FRAMING  
(NOT BY IMP SUPPLIER)

"OC-08" OUTSIDE CORNER  
W/ 10. x 0.75" PPH DP3 8" O/C  
(SET TRIM IN BUTYL SEALANT)

( ) ¼ - 14 x \_ HWH DP3 W/  
WASHER, PER PANEL AT  
EACH SECONDARY SUPPORT

NOTE: FIELD CUT STARTING PANEL  
AND ENDING PANEL AS REQUIRED  
AT CORNER TRANSITION.

"IC-05 " INSIDE CORNER W/  
POP RIVETS 12" O/C  
(SET TRIM IN BUTYL SEALANT)

PEEL & STICK BITUMEN MEMBRANE

½" DIAMETER BEAD  
OF BUTYL SEALANT

#

## CORNER TRANSITION - SCULPTED INSIDE

(PLAN VIEW)

DETAIL:

### CORNER TRANSITION - SCULPTED INSIDE

929 ALDRIDGE ROAD  
VACAVILLE, CA 95688  
TEL: (707) 359-2280  
FAX: (707) 359-2286  
WWW.AWIPANELS.COM

**All Weather**  
Insulated Panels



APPLICATION:  
VERTICAL WALL, COLD STORAGE  
AWIP DETAIL NUMBER:  
AVW-ACS-CT-004

DATE:  
09/30/25

DRAWN BY:  
MMF

SHEET:

1

OF  
1