

1/4 - 14 x 0.88" HWH DP1 6" O/C

"HRC-\_\_" METAL CLOSURE, REFER TO SHEET \_\_ FOR FASTENING INFORMATION

HR\_ OUTSIDE CLOSURE STRIP SET IN 1" x 3/16" BUTYL TAPE SEALANT AT TOP AND BOTTOM

FIELD-FILL W/ COMPRESSIBLE INSULATION (NOT BY IMP SUPPLIER)

"HE-\_H" HIGH EAVE TRIM

"WC-01" PANEL CLIP W/ ( ) 1/4 - 14 x \_ HWH DP3 W/O WASHER AT PANEL JOINT

POP RIVETS 12" O/C

1/2"

1" x 3/16" BUTYL TAPE SEALANT AT TOP AND BOTTOM

NOTE: BARE HRC- PROVIDED FOR PROJECTS WITH ROOF SLOPE ≤ 1:12 AND EAVE HEIGHT ≥ 20'.

(3) 1/4 - 14 x \_ HWH DP3 W/ WASHER, PER PANEL (SPACED EVENLY)

BUTYL TAPE SEALANT

BUTYL TAPE SEALANT (MARRY TO VERTICAL SEALANT)


HIGH EAVE STRUT (NOT BY IMP SUPPLIER)

BUTYL SEALANT AT VERTICAL JOINT

# # HIGH EAVE

(SECTION VIEW)

CLICK HERE



DETAIL:

## HIGH EAVE

APPLICATION:  
HR ROOF: COMMERCIAL & INDUSTRIAL  
AWIP DETAIL NUMBER:  
HRR-ACH-HE-001

929 ALDRIDGE ROAD  
VACAVILLE, CA 95688  
TEL: (707) 359-2280  
FAX: (707) 359-2286  
WWW.AWIPANELS.COM



DATE: 11/15/24

DRAWN BY: MMF

SHEET:

1

OF 1