

NOTE: FACE-CAULK AT VERTICAL REVEALS FROM BT- TRIM TO EAVE/RAKE TRIM TO CREATE A WEATHERTIGHT SEAL.

MARRIAGE BEAD

BUTYL SEALANT AT VERTICAL JOINT

"TF-02" TRANSITION FLASHING W/ 10. x 0.75" PPH DP3 12" O/C (SET TRIM IN BUTYL SEALANT)

"WC-01" PANEL CLIP W/ () 1/4 - 14 x _ HWH DP3 W/O WASHER AT PANEL JOINT

SECONDARY FRAMING (NOT BY IMP SUPPLIER)

"HRC-__" METAL CLOSURE FASTENED AT BOTTOM ONLY, REFER TO SHEET __ FOR FASTENING INFORMATION

HR_ OUTSIDE CLOSURE STRIP SET IN 1" x 3/16" BUTYL TAPE SEALANT AT TOP AND BOTTOM

(3) 1/4 - 14 x _ HWH DP3 W/ WASHER, PER PANEL (SPACED EVENLY)

SIKA FLEX ONE-PART POLYURETHANE SEALANT BY OTHERS (NOT BY IMP SUPPLIER)

"BT-07" FASCIA TRIM W/ 1/4 - 14 x 0.88" HWH DP1 12" O/C

"TF-01" TRANSITION FLASHING W/ 1/4 - 14 x 0.88" HWH DP1 6" O/C

1/2"


"HRC-__" METAL CLOSURE REFER TO SHEET __ FOR FASTENING INFORMATION

1" x 3/16" BUTYL TAPE SEALANT AT TOP AND BOTTOM

SECONDARY FRAMING (NOT BY IMP SUPPLIER)

HIGH EAVE TO WALL

(SECTION VIEW)



DETAIL: HIGH EAVE TO WALL	DATE:	10/23/23	SHEET:	1	OF	1
	APPLICATION:	HR ROOF, COMMERCIAL & INDUSTRIAL	DRAWN BY:	MMF		
929 ALDRIDGE ROAD VACAVILLE, CA 95688 TEL: (707) 359-2280 FAX: (707) 359-2286 WWW.AWIPANELS.COM		AWIP DETAIL NUMBER: HRR-ACH-HEW-002				
 All Weather Insulated Panels						