

IP44 Partition Wall

with InnovaCELL™ Technology

AWIP ALLOWABLE LOAD TABLE

IP44 Interior Partition Allowable Load Table (PSF) for Single Span at 5 PSF and L/120

Panel Strength, Deflection Limit and Temperature Difference Criteria

Exterior/Interior Profile	Panel Thickness	Panel Span (ft)			
		Δ T = 0°	Δ T = 35°	Δ T = 70°	Δ T =105°
Mesa	2"	20'-9"	Minimum 4" thick panels recommended for temperature-controlled conditions. Consult your technical services representative for more information		
	2.5"	24'-3"			
	3"	27'-6"			
	4"	33'-5"	29'-2"	25'-1"	21'-6"
	5"	38'-11"	34'-3"	29'-11"	25'-11"
	6"	44'-0"	39'-1"	34'-4"	30'-1"
	8"	53'-4"	47'-11"	42'-8"	37'-10"
Flat	2"	20'-5"	17'-1"	14'-1"	11'-7"
	2.5"	23'-10"	20'-3"	16'-11"	14'-1"
	3"	27'-0"	23'-2"	19'-7"	16'-7"
	4"	32'-11"	28'-8"	24'-8"	21'-2"
	5"	38'-5"	33'-9"	29'-5"	25'-6"
	6"	43'-5"	38'-6"	33'-11"	29'-8"
	8"	52'-9"	47'-4"	42'-2"	37'-4"

Notes:

1. Load span table is based on Allowable Stress Design (ASD).
2. Table is based on values derived from transverse load testing per ASTM E72.
3. Panel Properties are based on **26 gauge exterior** and **26 gauge interior** facings. Inquire about other gauges.
4. The deflection limit criteria is L/120.
5. Allowable spans are calculated based on a minimum 5 psf interior horizontal load per the International Building Code.
6. Safety Factor = 2.5 for buckling, 3.0 for core shear.
7. Panels must be supported at the base and top of panel.
8. Connections must be designed separately depending on type of support at panel ends.
9. Panel weights can be found on a separate Panel Weights Table.
10. Structural design of wall supports has not been considered and must be designed the support professional.
11. Thermal effects at specified Delta T have been applied to allowable single spans.
12. Consult your AWIP representative for project specific calculations.
13. Load tables are subject to change without notice - visit www.awipanel.com for the latest information.

IP44 Interior Partition Allowable Load Table (PSF) for Single Span at 10 PSF and L/180

Panel Strength, Deflection Limit and Temperature Difference Criteria

Exterior/Interior Profile	Panel Thickness	Panel Span (ft)			
		Δ T = 0°	Δ T = 35°	Δ T = 70°	Δ T =105°
Mesa	2"	13'-4"	Minimum 4" thick panels recommended for temperature-controlled conditions. Consult your technical services representative for more information		
	2.5"	15'-8"			
	3"	17'-10"			
	4"	21'-9"	18'-9"	16'-0"	13'-7"
	5"	25'-5"	22'-2"	19'-1"	16'-5"
	6"	28'-9"	25'-3"	22'-0"	19'-2"
	8"	34'-10"	31'-0"	27'-5"	24'-1"
Flat	2"	12'-10"	10'-7"	8'-7"	7'-1"
	2.5"	15'-1"	12'-7"	10'-5"	8'-8"
	3"	17'-2"	14'-6"	12'-2"	10'-3"
	4"	21'-1"	18'-2"	15'-5"	13'-2"
	5"	24'-8"	21'-5"	18'-6"	15'-11"
	6"	28'-0"	24'-7"	21'-4"	18'-7"
	8"	34'-1"	30'-3"	26'-9"	23'-6"

- Notes:
- 1. Load span table is based on Allowable Stress Design (ASD).
 - 2. Table is based on values derived from transverse load testing per ASTM E72.
 - 3. Panel Properties are based on **26 gauge exterior** and **26 gauge interior** facings. Inquire about other gauges.
 - 4. The deflection limit criteria is L/180.
 - 5. Allowable spans are calculated based on a minimum 10 PSF interior horizontal load.
 - 6. Safety Factor = 2.5 for buckling, 3.0 for core shear.
 - 7. Panels must be supported at the base and top of panel.
 - 8. Connections must be designed separately depending on type of support at panel ends.
 - 9. Panel weights can be found on a separate Panel Weights Table.
 - 10. Structural design of wall supports has not been considered and must be designed the support professional.
 - 11. Thermal effects at specified Delta T have been applied to allowable single spans.
 - 12. Consult your AWIP representative for project specific calculations.
 - 13. Load tables are subject to change without notice - visit www.awipanel.com for the latest information.



Scan for the most current product information



All Weather Insulated Panels

1 (888) 970-AWIP (2947)
awipanel.com
sales@awipanel.com



In accordance with ongoing efforts to improve our products and their performance, All Weather Insulated Panels reserves the right to change without notice the specifications contained herein. The contents herein are for general information and illustrative purposes only and are not intended to serve as any type of advice. Every effort is made to ensure the accuracy of the information included in this brochure and it is believed that the information contained herein is accurate and reliable as of the date of this publication. All Weather Insulated Panels does not warrant or represent the accuracy or reliability of any information included in this collateral. Any reliance of any information without consultation with All Weather Insulated Panels or a duly authorized representative shall be at the user's own risk. Copyright 2025 All Weather Insulated Panels— All rights reserved.