

HR3-W Allowable Load Table (PSF) for Three or More Spans

Panel Strength and Deflection Limit Criteria

Panel Thickness	Panel Span (ft)									
	3'-0"	3'-6"	4'-0"	4'-6"	5'-0"	5'-6"	6'-0"	6'-6"	7'-0"	7'-6"
1.5"	45	38	33	29	25	23	21	19	18	16
2.5"	79	67	58	51	45	41	37	34	31	29
3"	96	81	70	61	55	49	45	41	38	35
4"	97	82	71	62	56	50	45	42	38	36

Connection Strength Criteria - Fasteners with SW-02 Washers at Each High Rib

Fastening/ Support Thickness	Panel Thickness	Panel Span (ft)									
		3'-0"	3'-6"	4'-0"	4'-6"	5'-0"	5'-6"	6'-0"	6'-6"	7'-0"	7'-6"
(1) fastener per SW-02 Washer / Minimum 16 gauge	1.5"	46	42	36	32	29	26	24	22	20	19
	2.5"	50	43	37	33	29	26	24	22	20	19
	3"	50	43	37	33	29	26	24	22	20	19
	4"	50	43	37	33	29	26	24	22	20	19
(1) fastener per SW-02 Washer / Minimum 14 gauge	1.5"	46	46	46	43	38	34	31	29	27	25
	2.5"	66	56	49	43	39	35	32	29	27	25
	3"	66	56	49	43	39	35	32	29	27	25
	4"	67	57	49	44	39	35	32	29	27	25
(1) fastener per SW-02 Washer / Minimum 12 gauge	1.5"	46	46	46	46	46	46	46	46	43	40
	2.5"	107	91	79	70	62	56	51	47	44	41
	3"	107	91	79	70	63	57	52	47	44	41
	4"	107	91	79	70	63	57	52	47	44	41

Notes:

1. Load span table is based on Allowable Stress Design (ASD).
2. Table is based on values derived from transverse load testing per ASTM E72, ASTM E1592 and strength of fasteners.
3. Panel Properties are based on **26 gauge exterior** and **26 gauge interior** facings. Inquire about other gauges.
4. The lowest load between Panel Strength, Deflection Limit and Connection Strength shall be used to determine spans.
5. The deflection limit criteria is $L/180$.
6. Connection based on $\frac{1}{4}$ -14 or $\frac{1}{4}$ -20 DP3 or DP5 self-drilling fasteners with SW-02 washer installed into min. 16 gauge, 14 gauge or 12 gauge steel.
7. Maximum span for HR3-W is 7.5'.
8. Safety Factor = 2.5 for buckling, 3.0 for core shear, 2.0 for wall clip, 3.0 for fastening pullover/pullout.
9. Allowable loads are applicable to vertical or horizontal panel installation.
10. Panel weights can be found on a separate Panel Weights Table.
11. Structural design of wall supports has not been considered and must be designed the support professional.
12. Thermal effects from controlled environment and cold storage applications have not been considered.
13. Consult your AWIP representative for project specific calculations.
14. HR3-W Wall Panels are not FM Approved Products.
15. Load tables are subject to change without notice – visit www.awipanel.com for the latest information.



All Weather
Insulated Panels



Scan for the most current
product information

1 (888) 970-AWIP (2947)
awipanel.com
sales@awipanel.com



In accordance with ongoing efforts to improve our products and their performance, All Weather Insulated Panels reserves the right to change without notice the specifications contained herein. The contents herein are for general information and illustrative purposes only and are not intended to serve as any type of advice. Every effort is made to ensure the accuracy of the information included in this brochure and it is believed that the information contained herein is accurate and reliable as of the date of this publication. All Weather Insulated Panels does not warrant or represent the accuracy or reliability of any information included in this collateral. Any reliance of any information without consultation with All Weather Insulated Panels or a duly authorized representative shall be at the user's own risk. Copyright 2025 All Weather Insulated Panels—All rights reserved.