

FM Approved Roof Configurations

FM LISTING OVERVIEW

FM Rating	Panel Type	Panel Gauge Ext/Int	Min Purlin Gauge	Max Purlin Spacing	Fastening Type	RoofNav Assembly #
Class 1-60	SR	26/26	16	5'-0"	Standard	317601-0-0
Class 1-90	SR	24/26	16	5'-3"	Standard	278783-0-0
Class 1-105	SR	24/26	12	5'-0"	Standard	317600-0-0
Class 1-105	SR	26/26	16	5'-0"	Standard + EC-01	317604-0-0
Class 1-135	SR	24/26	14	4'-0"	Standard + EC-01	317605-0-0
Class 1-60	HR	26/26	16	5'-3"	Ribs 20" o.c.	222746-0-0

Notes:

1. Standard fastening for SR includes (3) 1/4-14 fasteners per SR-0X clip per joint per support. EC-01 clip is attached after installation and seaming of panels over the SR-0X clip location.
2. Standard fastening for HR includes (1) 1/4-14 fastener per SW-01 saddle washer assembly at a high-rib every 20" on center across the panel width per support.
3. Class 1 refers to the panels in respect to a Class 1 fire rating. The number after the "--" is the assembly wind rating in respect to wind load (PSF).



Scan for the most current product information



All Weather
Insulated Panels

1 (888) 970-AWIP (2947)
awipanel.com
sales@awipanel.com



In accordance with ongoing efforts to improve our products and their performance, All Weather Insulated Panels reserves the right to change without notice the specifications contained herein. The contents herein are for general information and illustrative purposes only and are not intended to serve as any type of advice. Every effort is made to ensure the accuracy of the information included in this brochure and it is believed that the information contained herein is accurate and reliable as of the date of this publication. All Weather Insulated Panels does not warrant or represent the accuracy or reliability of any information included in this collateral. Any reliance of any information without consultation with All Weather Insulated Panels or a duly authorized representative shall be at the user's own risk. Copyright 2025 All Weather Insulated Panels—All rights reserved.